

MODEL	400 CBAC	400 SB	400 SBS	400 CBACR	400 CBAC LN
Voeding	230 V (+6% -10%) 50 (60) Hz	230 V (+6% -10%) 50 (60) Hz	230 V (+6% -10%) 50 (60) Hz	230 V (+6% -10%) 50 (60) Hz	230 V (+6% -10%) 50 (60) Hz
Opgenomen vermogen	220 W	220 W	220 W	220 W	220 W
Opgenomen stroom	1 A	1 A	1 A	1 A	1 A
Rotatiesnelheid motor	1400 toeren/min	1400 toeren/min	1400 toeren/min	1400 toeren/min	1400 toeren/min
Lineaire snelheid zuigerstang	1 cm/s	1 cm/s	0,75 cm/s	1,5 cm/s	1,5 cm/s
Debiet van de pomp	1 l/min	1 l/min	0,75 l/min	1,5 l/min	1,5 l/min
Max. trek-/duwkracht	0-620 daN	0-620 daN	0-775 daN	0-465 daN	0-465 daN
Omgevingstemperatuur	-20°C ÷ +55°C	-20°C ÷ +55°C	-20°C ÷ +55°C	-20°C ÷ +55°C	-20°C ÷ +55°C
Oververhittingsbeveiliging wikkeling	120°C	120°C	120°C	120°C	120°C
Gewicht	8,6 kg	8,6 kg	8,6 kg	8,6 kg	10 kg
Type olie	FAAC HP OIL	FAAC HP OIL	FAAC HP OIL	FAAC HP OIL	FAAC HP OIL
Beschermingsgraad	IP 55	IP 55	IP 55	IP 55	IP 55
Afmetingen (LxBxH) in mm	1031 x 113 x 85 mm - lange versie 1285 x 113 x 85 mm	1031 x 113 x 85 mm - lange versie 1285 x 113 x 85 mm	1031 x 113 x 85 mm - lange versie 1285 x 113 x 85 mm	1031 x 113 x 85 mm - lange versie 1285 x 113 x 85 mm	1031 x 113 x 85 mm - lange versie 1285 x 113 x 85 mm