

## Vingerscanner Stedaparts

Standalone waterbestendige toegangscontrole vingerscanner en paslezer in 1  
Door de afmetingen zeer geschikt voor montage op de deurpost.

|   |  |
|---|--|
| <b>User Capacity</b>                    | 3000   |
| Fingerprint                             | 1000   |
| Card                                    | 2000   |
| <b>Operating Voltage</b>                | 12V DC   |
| Idle Current                            | < 45mA   |
| <b>Proximity Card Reader EM&amp;HID</b> |  |
| Radio Technology                        | 125KHz Proximity Card  |
| Read Range                              | 2~4 cm   |
| <b>Fingerprint Reader</b>               | Optical Fingerprint Module   |
| Resolution                              | 500DPI   |
| Identification time                     | <1S  |
| FAR                                     | <0.001%  |
| FRR                                     | <0.01%   |
| <b>Wiring Connections</b>               | Relay output,<br>exit button,<br>alarm,<br>door contact,<br>Wiegand output |
| <b>Relay</b>                            | One (NO, NC, Common)   |
| Adjustable Relay Output Time            | 0~99 Seconds (5 seconds default)   |
| Lock Output Load                        | 2 Amp Maximum  |
| <b>Wiegand Interface</b>                | Wiegand 26~44bits output   |
| Environment                             | Meets IP66   |
| Operating Temperature                   | -30°C ~ 60°C (-22°F ~ 140°F)--Default                                      |
| Operating Humidity                      | -40°C ~ 60°C (-40°F ~ 140°F)--Optional<br>10%RH ~ 99%RH                    |
| <b>Physical</b>                         | Zinc-Alloy   |
| Color                                   | Silver   |
| Dimensions                              | L128 x W48 x H26 (mm)  |
| Unit Weight                             | 400g   |

